

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 November 2003 (27.11.2003)

PCT

(10) International Publication Number
WO 03/098025 A1

(51) International Patent Classification⁷: **F02G 1/053**

(21) International Application Number: PCT/GB03/02080

(22) International Filing Date: 14 May 2003 (14.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0211121.9 15 May 2002 (15.05.2002) GB

(71) Applicant (for all designated States except US): **MICRO-GEN ENERGY LIMITED** [GB/GB]; 100 Thames Valley Park Drive, Reading, Berkshire RG6 1PT (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ALDERSON, John, Howard** [GB/GB]; Narrow Lane House, Coasthill, Crich, Matlock, Derbyshire DE4 5DS (GB). **CLARK, David,**


Anthony [GB/GB]; 4 Mill Dam, Hugglescote, Leicestershire LE67 2BU (GB). **HYDE, Julie, Patricia** [GB/GB]; 150 Barn Lane, Olton, Solihull, West Midlands B92 7LZ (GB). **LAMB, Jennifer, Jane** [GB/GB]; 86 Willmott Road, Sutton Coldfield, West Midlands B75 5NW (GB). **ALLDERIDGE, Heather,** [GB/GB]; 51 Derby Road, Aston-on-Trent, Derby, Derbyshire DE72 2AE (GB).

(74) Agents: **DRAPER, Martyn, John** et al.; Boulton Tennant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: A STIRLING ENGINE ASSEMBLY



(57) Abstract: A Stirling engine assembly comprising a Stirling engine (1) having a head (2). A burner (7) for providing heat to the engine head surrounds the head. A flexible seal (20) seals the interface between the engine and burner. A first liquid coolant circuit (25) is positioned between the burner and seal to reduce the heat transfer from the burner to the seal.

WO 03/098025 A1



(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

-1-

A STIRLING ENGINE ASSEMBLY

5 The present invention relates to a Stirling engine assembly, and, in particular to a Stirling engine assembly for use in a combined heat and power (chp) system primarily for use in a domestic environment.

10 The Stirling engine has a burner located around the heater head at the top of the engine. A problem for the Stirling engine-based chp system is the need to ensure that combustion gases do not pass downwards into the room-sealed unit enclosure, causing the accumulation of potentially harmful gases. Some form
15 of seal is therefore required between the Stirling engine and the burner.

When operating, the Stirling engine vibrates, due to its reciprocating components. A vibration
20 reduction system, incorporating various damping and absorbing components has brought the residual levels of vibration to a low level, but there is still enough to cause problems to any seal located between the vibrating engine and the stationary burner casing.
25 Some conventional seal designs are typically significantly stiffer than the engine suspension system and would, if used in the application, lead to unacceptable transmission of forces between the oscillating engine and the static burner components.
30 As such the seal design is required to be extremely robust, operate at high temperatures, and be capable of maintaining an adequate seal under all operating conditions, as defined by the gas appliance certification procedure.

35

Excessive wear, fatigue or degradation of such a seal would cause combustion gases to leak into the

-2-

unit enclosure, causing a hazard, and increasing noise levels. A seal design is therefore required that is flexible enough to cope with the relative motion (vertical, horizontal and rotational in nature) between engine and burner. In addition, this seal must be able to withstand the high temperatures associated with the burner gases, and must not be corroded by the gases involved.

One prior art design proposed by GE in 1979 (GE Semi-Annual Report 80SD54215) uses a PTFE seal. Such a seal is not suitable in a domestic environment as it introduces a potential hazard at the temperatures involved due to known toxic emissions from PTFE.

US 5,918,463 proposes the use of a ceramic seal. However, ceramic is a material which is susceptible to failure due to vibration.

According to the present invention a Stirling engine assembly comprises a Stirling engine having a head, a burner for providing heat to the engine head, a flexible seal between the engine and burner, and a first liquid coolant circuit between the burner and seal positioned to reduce the heat transfer from the burner to the seal.

By providing a coolant circuit, the temperature that the seal must withstand can be significantly reduced such that conventional seal materials can be used.

The liquid for the first liquid coolant circuit can be provided from any suitable source. However, the Stirling engine has a cooler with a second liquid coolant circuit. It is therefore convenient to feed the first and second liquid coolant circuits with

-3-

common liquid.

With such an arrangement, the first and second liquid coolant circuits may be arranged in parallel.

5 In this case, the flow of liquid to the first liquid coolant circuit will generally be a bleed flow from the main flow of liquid to the second coolant circuit. Alternatively, the flow to the first and second liquid coolant circuits may be arranged in series. In this
10 case, it is preferable for the liquid to flow around the second coolant circuit prior to the first coolant circuit to maintain the cooler at as low a temperature as possible.

15 If the first liquid coolant circuit is positioned radially inwardly of the seal, this can increase the distance between the burner and seal and allow the seal to be positioned in a region where it is more readily cooled by the surrounding air.

20

In addition to the first liquid coolant circuit, it can be advantageous to provide additional ways of reducing the heat transfer from the burner to the seal. For example, a tortuous path can be provided
25 for gas flowing from the burner to the seal. Alternatively or additionally, insulation may be provided to reduce heat transfer from the burner to the seal. Both of these objectives can be achieved by packing the space beneath the burner between a burner
30 housing and the head of the Stirling engine with a fibrous insulating material.

The flexible seal may be any material suitable for the job. However, the invention allows the use of
35 conventional, commercially available sealing materials which are capable of withstanding a maximum temperature of less than 350°C, such as a silicon

-4-

rubber sealing material.

5 A further way of maintaining the seal as at low a
temperature as possible is for the flexible seal to
extend into the first liquid coolant circuit. This
brings the coolant into direct contact with the
flexible seal. Preferably, the first liquid coolant
circuit has, surrounding the engine, an open annular
channel section and an annular plate across the open
10 annular section, wherein the seal is sandwiched
between the channel section and plate. This allows
the coolant into contact with the seal as referred to
above, and also provides a way of attaching the seal
to the coolant circuit, as well as sealing the coolant
15 circuit, thereby eliminating the need for a further
sealing element.

Examples of a Stirling engine assembly in
accordance with the present invention will now be
20 described with reference to the accompanying drawings,
in which:

Fig. 1 is a schematic diagram of a first Stirling
engine assembly;
25

Fig. 2 is a cross-section showing a portion of
the Stirling engine head and the combustion seal of
the first engine;

30 Fig. 3 is a perspective view of the liquid
passage circuit of Fig. 2; and

Fig. 4 is a cross-section through the liquid
coolant passage of Fig. 3.
35

Most aspects of the Stirling engine assembly
shown in Fig. 1 are well known in the art and will be

-5-

described only briefly here.

The Stirling engine 1 is a linear free piston
Stirling engine and comprises an engine head 2 beneath
5 which is a cooler 3 and an alternator 4. The
Stirling engine 1 is suspended from a casing (not
shown) by a plurality of springs 5.

Ambient air is drawn in through flue 6, preheated
10 by combustion gases and mixed with combustible fuel
before being ignited at burner 7 to heat the engine
head 2. A plurality of fins 8 enhance the heat
transfer to the head. Combustion gases preheat the
incoming air/fuel mixture and are then fed to the heat
15 exchanger 9 to heat water in a domestic central
heating circuit 10. A supplementary burner 11 is
provided to supply additional heat to the domestic
central heating circuit 10 should the demand for hot
water exceed that which can be supplied by the
20 Stirling engine 1 alone. A fan 12 supplies the two
burners 7, 11 and a splitter valve 13 controls the
split of air between the burner 7 and supplementary
burner 11. This, together with the control of the fan
speed, allows control of the amount of air fed to each
25 burner.

The hot water in the domestic central heating
circuit 10 then circulates around the domestic central
heating system where it loses its heat through the
30 domestic radiators or it is used to meet the domestic
hot water requirement. The cooled liquid then returns
to the Stirling engine assembly along line 10A. It is
known for this water to then be used to cool the
engine cooler 3 resulting in a slight temperature rise
35 in the water before returning to the heat exchanger 9
along line 14 to be heated to the full temperature
required by the central heating system. The present

-6-

invention operates in this way. However, it makes additional use of the incoming cool water in line 10A as described in greater detail below.

5 As shown in Figs. 2 to 4, a seal 20 is provided to seal a space between burner casing 21 and an annular flange 22 welded to the head 2 of the Stirling engine 1. The coolant channel is provided by a cast aluminium channel element 25 having an inverted U
10 cross-section. The seal 20 extends across the full width of the bottom of this channel element and is sandwiched between the bottom of the channel element 25 and an annular plate 26 which is held in place by a plurality of bolts 27. The channel has an inlet 28
15 and outlet 29. This arrangement of the seal and channel fulfils a number of functions. It provides a way of attaching the seal with respect to the burner casing, it provides a way of efficiently cooling the seal as a large part of the seal element is in direct
20 contact with the water circulating in the channel 25, and it provides a way of sealing the channel without the need for a separate sealing element. The seal 20 is secured into an annular groove 30 by a seal retaining clip 33.

25

 As well as the circulation of coolant fluid around the channel 25, there are a number of other measures which have been taken to reduce the temperature of the seal as will be apparent from Fig.
30 2. A ceramic insulation ring 24 which is made up of two semicircular pieces fills the majority of the space between the burner 7 and the cooling channel 25. The ring is also positioned so that there is a tortuous path from the burner to the seal 20. It will
35 also be noted that the exposed part of the seal 20 is positioned radially outwardly of the channel 25, and is also exposed to the surrounding air. This allows

-7-

cooling of the seal by the surrounding air, and also enhances the effect of the tortuous path referred to above.

5 In order to assemble the engine assembly, the engine is provided as a burner module and an engine module. The engine module includes the engine 1, the annular flange 22, the seal 20, the seal retaining clip 33, the cooling channel 25, annular plate 26,
10 bolts 27 and an annular engine support bracket 40. It should be noted that the engine support bracket 40 extends beyond the extent shown in Fig. 2 and is independently supported, such that the weight of the channel 25 is supported through the engine support
15 bracket 40 and not through the seal 20. The burner module includes the burner 7, and to this is attached an annular spacer 41 and an annular support bracket 42 via circumferentially arranged bolts 43. With the burner module in place, the engine module is inserted
20 up into the burner module until the engine support bracket 40 abuts the main support bracket 42. The interface between these is sealed by a gasket 44.

25 In this example, the flow around the annular water jacket 25 is in series with the flow around the cooler 3. As shown in Fig. 1, the cool liquid in line 10A circulates around the cooler 3 in a known manner, before flowing along line 26 to the annular water jacket 25. The water leaving the annular water jacket
30 25 then travels along line 14 to the heat exchanger 9.

35 Water flows into the annular water jacket 25 from the Stirling engine cooler 3. Under normal operation, the temperature of the water is therefore in the region of 50°C as it enters the jacket. Heat is removed from the burner housing 21, maintaining the seal material at an acceptable temperature. This

-8-

allows the use of more effective sealing materials, which would degrade at the temperatures that would be encountered in the absence of cooling (potentially in excess of 350°C housing temperature). Such sealing materials could be, for example, silicon rubber, or a fluoroelastomer such as Viton or PTFE.

In some circumstances the dwelling does not require heat, but the Stirling engine is operating to generate power. In such a situation, water will flow through Stirling engine cooler 3, around the seal, and heat exchanger 9, but then it will be routed through a bypass and flow back to the engine cooler without travelling around the domestic hot water system. The heat exchanger 9 will be operating to cool the water as no additional heat will be added here. Where supplementary burner 11 and Stirling engine burner 7 use separate fans, the supplementary burner fan could be operated to aid this heat removal as in patent application GB 0130378.3. Water temperatures within the cooling system will, however, be higher, usually up to 80°C, as no heat is being lost to the dwelling. Even at this temperature level the seal area will be adequately cooled, and no excessive material degradation will occur.

An additional benefit of the liquid cooled seal design is the recovery of additional heat into the cooling water. The heat transferred in this area would normally raise the temperature of the air inside the chp unit enclosure. Air is circulated around the enclosure by the forced draft as it is drawn into the air intake of the supplementary burner 11. Cooling for the external surfaces of the Stirling engine and the alternator 4 is required to maintain an acceptable temperature for internal components, and where the surrounding air is being heated around the seal area,

-9-

this reduces the cooling effectiveness of the circulating air. By removing this heat in the water system, the air cooling the engine/alternator is at a lower temperature and therefore provides a more effective degree of cooling. This will extend the life of temperature-sensitive components such as the alternator magnets, and potentially also increase the generating efficiency of the alternator.

Although the engine is shown in the illustrated example, it could equally be applied to a non-vertical engine, such as a horizontal engine. It is also equally applicable to an engine mounted in an inverted configuration to that shown.

CLAIMS

1. A Stirling engine assembly comprising a Stirling engine having a head, a burner for providing heat to the engine head, a flexible seal between the engine and burner, and a first liquid coolant circuit between the burner and seal positioned to reduce the heat transfer from the burner to the seal.
5
2. A Stirling engine assembly according to claim 1, wherein the Stirling engine further comprises a cooler with a second liquid coolant circuit fed with liquid common to the first liquid coolant circuit.
10
3. A Stirling engine assembly according claim 2, wherein the first and second liquid coolant circuits are arranged in parallel.
15
4. A Stirling engine assembly according to claim 2, wherein the first and second liquid coolant circuits are arranged in series.
20
5. A Stirling engine assembly according to claim 1 or claim 2, wherein the first liquid coolant circuit is positioned radially inwardly of the seal.
25
6. A Stirling engine assembly according to any one of the preceding claims, wherein in a torturous path is provided for gases flowing from the burner to the seal.
30
7. A Stirling engine assembly according to any one of the preceding claims, wherein insulation is provided to reduce heat transfer from the burner to the seal.
35
8. A Stirling engine assembly according to claim 6

-11-

and claim 7, wherein fibrous insulating material is packed into the space beneath the burner between a burner housing and the head of the Stirling engine.

5 9. A Stirling engine assembly according to any one of the preceding claims, wherein the seal is a silicon rubber sealing material.

10 10. A Stirling engine assembly according to any one of claims 1 to 8, wherein the seal is a fluoroelastomer sealing material.

15 11. A Stirling engine assembly according to any one of the preceding claims, wherein the seal can withstand a maximum temperature of less than 350°C.

20 12. A Stirling engine according to any one of the preceding claims, wherein the flexible seal extends into the first liquid coolant circuit.


25 13. A Stirling engine according to claim 12, wherein the first liquid coolant circuit has, surrounding the engine, an open annular channel section and an annular plate across the open annular section, wherein the seal is sandwiched between the channel section and plate.

30

35


1/3

FIG. 1.



2/3

FIG. 2.



3/3

FIG. 3.





FIG. 4.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/02080

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F02G1/053

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F02G F02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 573 320 A (KRALICK JAMES) 4 March 1986 (1986-03-04) column 2, line 57 - column 3, line 17; claim 3; figures 1,2 ----	1
A	US 4 365 474 A (CARLOVIST STIG G) 28 December 1982 (1982-12-28) column 7, line 11 - line 14; claim 4; figure 5 ----	1
A	US 3 959 971 A (MEKARI MILAD H) 1 June 1976 (1976-06-01) column 2, line 3 - line 34; figure 5 -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

* & * document member of the same patent family

Date of the actual completion of the international search

12 August 2003

Date of mailing of the international search report

21/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Tietje, K

INTERNATIONAL SEARCH REPORT
Information on patent family members

Int: ional Application No
PCT/GB 03/02080

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4573320	A	04-03-1986	CA 1246346 A1 DE 3680854 D1 EP 0220199 A1 JP 63500111 T WO 8606793 A1	13-12-1988 19-09-1991 06-05-1987 14-01-1988 20-11-1986
US 4365474	A	28-12-1982	SE 417448 B DE 3017641 A1 DE 3050315 A1 GB 2051961 A ,B JP 1262516 C JP 56012034 A JP 59038426 B SE 7905378 A	16-03-1981 15-01-1981 22-07-1982 21-01-1981 25-04-1985 05-02-1981 17-09-1984 20-12-1980
US 3959971	A	01-06-1976	NONE	

PUB-NO: WO003098025A1
DOCUMENT-IDENTIFIER: WO 3098025 A1
TITLE: A STIRLING ENGINE ASSEMBLY
PUBN-DATE: November 27, 2003

INVENTOR-INFORMATION:

NAME	COUNTRY
ALDERSON, JOHN HOWARD	GB
CLARK, DAVID ANTHONY	GB
HYDE, JULIE PATRICIA	GB
LAMB, JENNIFER JANE	GB
ALLDERIDGE, HEATHER	GB

ASSIGNEE-INFORMATION:

NAME	COUNTRY
MICROGEN ENERGY LTD	GB
ALDERSON JOHN HOWARD	GB
CLARK DAVID ANTHONY	GB
HYDE JULIE PATRICIA	GB
LAMB JENNIFER JANE	GB
ALLDERIDGE HEATHER	GB

APPL-NO: GB00302080
APPL-DATE: May 14, 2003

PRIORITY-DATA: GB00211121A (May 15, 2002)

INT-CL (IPC) : F02G001/053

EUR-CL (EPC) : F02G001/053 , F02G001/055

ABSTRACT:

CHG DATE=20031210 STATUS=O>A Stirling engine assembly comprising a Stirling engine (1) having a head (2). A burner (7) for providing heat to the engine head surrounds the head. A flexible seal (20) seals the interface between the engine and burner. A first liquid coolant circuit (25) is positioned between the burner and seal to reduce the heat transfer from the burner to the seal.